

4K Ultra HD (NDI) AI Tracking PTZ Camera



4K Ultra HD AI Tracking PTZ Camera

4K Ultra HD NDI AI Tracking PTZ Camera

Key Features

- 4K Ultra HD Image, with resolution up to 4K@60fps
- 12X/25X/30X optical zoom lens
- Support PoE
- Support AI tracking, with real-time tracking and area tracking optional
- Fast, accurate and stable auto focus
- Low Noise and High SNR
- Multiple interfaces with HDMI, USB, LAN and SDI
- Multiple Audio/Video Compression Standard
- Multiple control port and control protocol
- Multiple Network Protocol include ONVIF, RTSP, RTMP, VISCA
- 4K Ultra HD NDI AI Tracking PTZ Camera support NDI HX3


Specification

Connectors	Video (OUT)	HDMI	1×HDMI-A		
		SDI	1×BNC		
		USB	1×USB-A		
		LAN (Support PoE)	1×RJ45		
	Audio (IN)		1×3.5mm Stereo Jack		
Communication	RS232 In/Out		2×DIN 8		
	RS422 (RS485)		1×4Pin Terminal		
Power			1×DC Jack		
Performance	Camera	Optical Zoom	12X	25X	30X
		Aperture	F1.8 ~F3.56±5%	F1.61 ~F5.19±5%	F1.35 ~ F4.6±5%
		Focus	f=3.85 mm ~ 43.06 mm ±5%	7.1 mm ~171.95 mm ±5%	6.91 mm ~214.21 mm ±5%
		View Angle	Horizontal: 7.59°(tele)~80.4°(wide) Tilt:4.6°(tele)~50.0°(wide)	Horizontal: 2.5°(tele)~59.2°(wide) Tilt: 1.4°(tele)~ 34.6°(wide)	Horizontal: 2.5°(tele)~59.2° (wide) Tilt: 1.4° (tele)~ 34.6°(wide)
		Image Sensor	1/2.5" SONY CMOS	1/1.8" SONY CMOS	1/1.8" SONY CMOS
		Digital Zoom	8X		
		Effective Pixels	8.51m,16:9		
		Illumination Min	0.05 lux (F1.8, AGC ON)		
		DNR	3D DNR		
		White Balance	Auto / Manual/ One Push/ Specified color temperature		
	Focus Mode	Auto / Manual/ One Push			
	Explosure Mode	Auto / Manual / Shutter Priority / Iris Priority / Whiteness Priority			
	Shutter Speed	1/25 ~ 1/10000			
	Dynamic range	OFF/ Dynamic level adjustment			
	BLC	ON/OFF			
Video Adjustment	Brightness/Color/Saturation/Contrast/Sharpness/B/W mode				
SNR	≥50dB				
Pan-and-Tilt Parameter	Pan/Tilt Rotation	-110°~+110°/-30°~+30°			
	Pan/Tilt Control Speed	0.1~100°/S ; 0.1~70°/S			
	Preset Speed/Numbers	Pan:78.8°/S, Tilt:31.7°/S; Up to 255 preset positions (10 remote control)			
Audio Compression Format	AAC,MP3,G.711A				
Video Compression Format	LAN:H.264, H.265 USB: MJPG, H.264, H.265, YUY2, NV12				
Output Resolutions	HDMI	3840*2160P60/50/25/59.94/29.97 1080P60/50/25/59.94/29.97 1080i60/50/59.94 1080P@30fps 720P@60fps 720P@50fps 720P60/50/59.94			
	SDI USB YUY2/NV12 MJPEG/H.264/H.265	1080P60/50/25/59.94/29.97 1080i60/50/59.94 1080P@30fps 720P@60fps 720P@50fps 720P60/50/59.94 640*480 640*360 480*270 320*180P30/25 1920*1080 1600*896 1280*720 1024*576 960*540 800*600 800*448 720*576 720*480 640*480 640*360 480*270 352*288 320*240P60/50/30/25 3840*2160P30			
Control Protocol	VISCA Pelco-D Pelco-P				
Baud Rate(bps)	115200 38400 9600 4800 2400bps				
Network Protocol	RTSP RTMP ONVIF VISCA				
Power	Input Voltage	DC12V			
	Max Power	<12W			
Working Environment	Temperature	-10℃ ~ 50℃			
	Humidity	20% ~ 80%			
Physical	Weight	Net	1.7kg		
		Package	3.5kg		
	Dimension	Net	220mm×144mm×159mm		
Package		275mm×260mm×350mm			

Order Codes

Product Code	Model
981-0011-85-0	RGB12X-UPAI-BK 12X 4K Ultra HD AI Tracking PTZ Camera
981-0011-86-0	RGB12X-UNAI-BK 12X 4K Ultra HD NDI AI Tracking PTZ Camera
981-0011-83-0	RGB25X-UPAI-BK 25X 4K Ultra HD AI Tracking PTZ Camera
981-0011-84-0	RGB25X-UNAI-BK 25X 4K Ultra HD NDI AI Tracking PTZ Camera
981-0011-87-0	RGB30X-UPAI-BK 30X 4K Ultra HD AI Tracking PTZ Camera
981-0011-88-0	RGB30X-UNAI-BK 30X 4K Ultra HD NDI AI Tracking PTZ Camera

Dimension



* There is no standard bracket for this PTZ. If necessary, please contact RGBlink sales for additional orders.

Tel: +86-592-5771197 | Fax: +86-592-5788216 | E-mail: sales@rgbink.com

Headquarter: Room 601A, No. 37-3 Banshang community, Building 3, Xinke Plaza, Torch Hi-Tech Industrial Development Zone, Xiamen, China

Specifications are correct at time of printing and subject to change or alteration without notice.

